



REFRIGERATORS, FREEZERS & WARMERS



Continental[®]
Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS

Roll-Ins & Roll-Thrus

Refrigerators, Freezers & Warmers

Our Designer Line models are equipped with both top and side air distribution ducts which allow for constant, uniform temperature throughout the cabinet.

Functionality

The refrigeration/heating systems on our Designer Line Roll-Ins & Roll-Thrus are accessible on top of the cabinet and separate from the food zone, increasing food storage capacity.

Performance & Reliability

Performance-run tested for a minimum of 12 hours providing a highly sophisticated temperature analysis recording, exclusive to each cabinet.



FLEXIBILITY

Modifications Made Easy.

At Continental Refrigerator, we know the foodservice industry is an ever-changing environment. We are reminded of this every day through feedback from our customers, both directly and through our network of representatives. In fact, customer feedback has often lead to our custom engineering modifications becoming standard product features.

For this reason, we pride ourselves in delivering feature-rich refrigeration equipment solutions designed specifically for the commercial foodservice market. Whether it's kitchen ambient, food safety, limited space or storage challenges, our products are packed with flexible options that provide **real** operator benefits out of the box. This flexibility, a key differentiator of our products, enables our customers to modify base product features strategic to the way they operate their kitchen or bar environment.

Shown: DL2RI-RT



Optional Models:

- SA: Stainless steel exterior, aluminum interior
- SS: Stainless steel exterior & interior

Consult factory for other modifications

www.continentalrefrigerator.com

Standard Features & Specifications

Standard Features

- Stainless steel front, aluminum end panels & interior
 - Self contained, performance-rated "plug" refrigeration system
 - Unique air flow distribution ducts
 - Environmentally-safe R-290 refrigerant** (refrigerators & 1-section freezers)
 - Environmentally-safe R404A refrigerant (2-section freezers)
 - Removable, stainless steel rackguides
 - Removable, stainless steel ramps
 - Reinforced stainless steel floor
 - 3" Non-CFC polyurethane foam insulation
 - Smooth, polished chrome workflow door handles
 - Cam-action, lift-off hinges
 - Automatic, hot gas condensate evaporator
 - Magnetic snap-in door gaskets
 - Cylinder lock in each door
 - Self-closing doors
 - LED interior lighting (except 1-section models)
 - Electronic controller w/ digital display & hi-low alarm
 - Expansion valve system** (refrigerators & freezers)
 - Warmers Only**
90°F to 180°F temperature range
 - Automatic interior lighting (except 1-section models)
- Note: racks not supplied*

Refrigerators

Standard Height Roll-In Models (Door Opening 27 3/8 W x 66 1/2 H)¹

MODEL TYPE	STD	"-SA"	"-SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
66" RACK CAPACITY	D1RIN	DL1RINSA	D1RINSS	35 1/4 x 35 3/8 x 86	2560	1/3+	455
	D2RIN	D2RINSA	DR2INSS	68 1/2 x 35 3/8 x 86	4010	1/2	730

Standard Height Roll-Thru Models

66" RACK CAPACITY	D1RNRT	D1RINSART	D1RINSSRT	35 1/4 x 38 3/4 x 86	2560	1/3	523
	D2RNRT	D2RINSART	DL2RINSSRT	68 1/2 x 38 3/4 x 86	4010	1/2	840

Extra-High Roll-In Models (Door Opening 27 3/8 W x 72 1/2 H)²

72" RACK CAPACITY	D1RINE	D1RINSAE	D1RINSSE	35 1/4 x 35 3/8 x 92	2980	1/2	475
	D2RINE	D2RINSAE	D2RINSSE	68 1/2 x 35 3/8 x 92	5930	3/4 ^s	770

Extra-High Roll-Thru Models

72" RACK CAPACITY	D1RINRTE	D1RINSARTE	D1RINSSRTE	35 1/4 x 35 3/8 x 92	2980	1/2	540
	D2RINRTE	D2RINSARTE	D2RINSSRTE	68 1/2 x 35 3/8 x 92	5930	3/4 ^s	880

Freezers (0°F)

Standard Height Roll-In Models (Door Opening 27 3/8 W x 66 1/2 H)¹

MODEL TYPE	STD	"-SA"	"-SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
66" RACK CAPACITY	D1FIN	D1FINSA	D1FINSS	35 1/4 x 35 3/8 x 86	3530	3/4	455
	DL2FI	DL2FI-SA	DL2FI-SS	68 1/2 x 35 3/8 x 86	4150	1	730

Standard Height Roll-Thru Models

66" RACK CAPACITY	D1FINRT	D1FINSART	D1FINSSRT	35 1/4 x 38 3/4 x 86	3530	3/4	523
	DL2FI-RT	DL2FI-SA-RT	DL2FI-SS-RT	68 1/2 x 38 3/4 x 86	4150	1	840

Extra-High Roll-In Models (Door Opening 27 3/8 W x 72 1/2 H)²

72" RACK CAPACITY	D1FINE	D1FINSAE	D1FINSSE	35 1/4 x 35 3/8 x 92	3530	3/4	475
	DL2FI-E	DL2FI-SA-E	DL2FI-SS-E	68 1/2 x 35 3/8 x 92	4150	1	770

Warmers

Standard Height Roll-In Models (Door Opening 27 3/8 W x 66 1/2 H)¹

MODEL TYPE	STD MODELS	"-SA"	"-SS"	EXTERIOR DIMENSIONS INCHES W x D x H	TOTAL WATTAGE	SHIP WEIGHT**
66" RACK CAPACITY	DL1WI	DL1WI-SA	DL1WI-SS	35 1/4 x 35 3/8 x 86	1500 [§]	360
	DL2WI	DL2WI-SA	DL2WI-SS	68 1/2 x 35 3/8 x 86	3000 [§]	625

Standard Height Roll-Thru Models

66" RACK CAPACITY	DL1WI-RT	DL1WI-SA-RT	DL1WI-SS-RT	35 1/4 x 35 3/8 x 86	1500 [§]	414
	DL2WI-RT	DL2WI-SA-RT	DL2WI-SS-RT	68 1/2 x 35 3/8 x 86	3000 [§]	719

Extra-High Roll-In Models (Door Opening 27 3/8 W x 72 1/2 H)²

72" RACK CAPACITY	DL1WI-E	DL1WI-SA-E	DL1WI-SS-E	35 1/4 x 35 3/8 x 92	1500 [§]	380
	DL2WI-E	DL2WI-SA-E	DL2WI-SS-E	68 1/2 x 35 3/8 x 92	3000 [§]	665

Extra-High Roll-Thru Models

72" RACK CAPACITY	DL1WI-RT-E	DL1WI-SA-RT-E	DL1WI-SS-RT-E	35 1/4 x 35 3/8 x 92	1500 [§]	440
	DL2WI-RT-E	DL2WI-SA-RT-E	DL2WI-SS-RT-E	68 1/2 x 35 3/8 x 92	3000 [§]	775

¹ Maximum rack size including wheels 27" W x 29" D x 66 1/4" H (racks not included)

² Maximum rack size including wheels 27" W x 29" D x 72" H (racks not included)

** Ship Weight for "SA" and "SS" models is on average 10% higher than Std models.

Refer to Specification Sheet for Shipping Weight of these models.

BTU/HR Rating @ +25°F, 90°F ambient

Extra long, 10 ft. cord and plug attached (115-60-1 volts)

[§] No cord and plug attached (115/208-230-60-1 volts)

- Chrome or stainless steel shelves
- Epoxy-coated steel shelves (refrigerator & freezers)
- Rehinging of doors (consult factory)
- Correctional facility package
- Custom laminates
- Stainless steel case back
- Half doors

Correctional Facility Package



Coverless hinges



Security screws



Locking hasp (lock not included)



Stainless steel mesh security cover

Engineering, Manufacturing & Quality Control



Unique air flow distribution ducts



Plug refrigeration system

Continental Refrigerator engineers builds our Roll-Ins and Roll-Thrus to meet the most stringent specifications demanded by consultants and service operators. All cabinets are constructed of top quality materials and components, attributing to their genuine ruggedness and durability. Roll-Ins and Roll-Thrus are designed with enhancements to endure everyday use in typical commercial kitchen environments.

Prior to factory shipping, all models are performance-run tested for a minimum of 12 hours, providing a highly sophisticated temperature analysis recording, exclusive to each individual cabinet. This recording is then supplied, along with the unit's operation manual, for the customer. A final leak test, vibration check, noise level and visual examination is made by our quality control team, to assure a superior product is shipped from our factory.

Air Flow

All models are equipped with both top and side air distribution ducts to keep product load at a uniformly constant temperature.

“Plug” Refrigeration

Designer Line Roll-In and Roll-Thru Refrigerators and Freezers utilize a “Plug” refrigeration system where the assembly is outside the food storage zone. The “Plug” system can be removed for servicing, cleaning, or converting from a refrigerator to freezer in the field.

Condensate water goes into a drain pan constructed with corrosion resistant 300 Series stainless steel. The condensate water is then evaporated by a non-electric, corrosion resistant 300 Series stainless steel hot gas discharge condensate loop.

Product design and specifications are subject to change without prior notice.

How to Buy

LOCAL SALES REPRESENTATIVES			STATES COVERED
Wyllie Marketing	Weymouth, MA	(781) 340-6157	ME, RI, NH, MA, VT, CT
Link 2 Hospitality Solutions	Rochester, NY	(585) 254-1780	Upstate NY
Pecinka Ferri Associates	Fairfield, NJ	(973) 812-4277	N. NJ, New York City
Schmid Dewland & Associates	Marlton, NJ	(856) 783-3400	E. PA, DE, S. & Central NJ
Link 2 Hospitality Solutions	Bridgeville, PA	(412) 341-2020	W. PA, W. VA (except Panhandle)
High Sabatino Associates, Inc.	Jessup, MD	(301) 470-7051	DC, MD, VA, W. VA (Panhandle)
Stiefel Associates, Inc.	Lansing, MI	(517) 393-3019	MI (except Upper Peninsula)
Dick Stanley & Associates	Pickerington, OH	(800) 833-0797	OH, KY
Gabriel Group	Fishers, IN	(800) 832-6442	IN
Jay Mark Group, LTD	Elk Grove Village, IL	(847) 545-1918	N. IL
North Star Agency	Plymouth, MN	(763) 545-1400	MN, ND, SD
Mirkovich & Associates	Waukesha, WI	(630) 792-0080	WI, MI (Upper Peninsula)
Select Marketing	St. Louis, MO	(314) 961-3332	MO, KS, IA, NE, S. IL
Master Marketing Carolina	High Shoals, NC	(704) 860-0092	NC, SC
Pro-Quip Foodservice	Little Rock, AR	(501) 221-7120	AR, LA, MS, W. TN (W. of Tenn. River)
The Veitch Group	Ft. Lauderdale, FL	(954) 316-6162	FL (except Panhandle)
Merkolat	Davie, FL	(561) 594-7153	Latin America, Caribbean
Carman-Girard Associates	Atlanta, GA	(770) 457-6548	AI, FL (Panhandle), GA, E. TN (E. of Tenn River)
Ignite Foodservice Solutions	Denver, CO	(303) 433-0124	CO, S. ID, MT, UT WY
Roller & Associates	Seattle, WA	(206) 547-3555	WA, OR, AK, N. ID
Foodservice Equipment Agents	Anaheim, CA	(714) 693-3329	AZ (Bull Head City), S. CA, S. NV
Inform Marketing Group	Walnut Creek, CA	(510) 337-0420	N. CA, N. NV
Ignite Foodservice Solutions	Phoenix, AZ	(303) 433-0124	AZ (except Bull Head City), NM, TX (El Paso)
Forbes Hever & Wallace, Inc.	Coppell, TX	(972) 219-8898	OK, TX (except El Paso)



A Division of National Refrigeration & Air Conditioning Products

Continental Refrigerator | Local: (215) 244-1400
 539 Dunksferry Road | Toll Free: (800) 523-7138
 Bensalem, PA 19020 | Fax: (215) 244-9579

www.continentalrefrigerator.com

Continental[®]

Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS



PROUDLY
 DESIGNED & ASSEMBLED
 IN THE U.S.A.